



Putting Confidence in Ultrasound

AH-2020 Preamplifier

The AH-2020 Preamplifier is the ultimate combination of performance and features. This preamplifier has two gain settings, selectable at the oscilloscope by either a switch or a TTL signal. Designed as an electronic and mechanical match for Onda hydrophones, the AH-2020 has only one coaxial cable going to the oscilloscope. It has a superb frequency response, low noise and high stability, which make it ideal for ultrasonic acoustic intensity measurements.

Features

- Dual Gain for >75dB dynamic range
- Flat frequency response
- Fully immersible
- Only one cable in the tank
- Waterproof mating to Onda hydrophones
- Compatible with any hydrophone
- Overload protection

Available in two different bandwidths:

- **AH-2020-025** 50 KHz - 25 MHz
- **AH-2020-100** 50 KHz - 100 MHz

Technical Specifications

- Voltage Gain: Hand or TTL switchable 0 or 20 dB
- Input Impedance: 1 M Ω in parallel with 8 pF
- Output Impedance: 50 Ω
- Max Output into 50 Ω : 1.2 Vpp
- Power Consumption: preamp 0.6 W, total 2 W

A Precision Gain and Input Capacitance calibration certificate is provided with each device.

Specifications are subject to change without notice.



AH-2020 Preamplifier





AH-2020 preamplifier with HGL hydrophone



Amplifier is supplied in a kit with Universal Power Supply, DC Block, 1m coaxial cable and calibration certificate.


Typical Gain Plots



Mechanical Specifications

Weight: 36 g

Material: Hermetically sealed stainless steel body.



ONDA

592 Weddell Drive, Suite 7, Sunnyvale, CA 94089, USA | Tel: 408.745.0383 | Fax: 408.745.0956 | www.ondacorp.com

取扱店:



ゼネレクス GENEREX
有限会社 エヴィック産業
 211-0016 川崎市中原区市ノ坪 107
 Tel 044-712-6770 Fax 044-411-2855
 E-Mail: s-mikami@generex.co.jp
<http://www.generex.co.jp>